




ELECTRONICS

Samsung Secret

Product Information

DATE : 28. Jul. 2010**SAMSUNG TFT-LCD****MODEL : LTA400HM08**

The Information Described in this Specification is Preliminary and can be changed without prior notice

| | | | |
|---|-----------------------|-------------------------------|-----------------------|
| APPROVAED BY  | DATE 28. Jul, 2010 | PREPARED BY Jeong-Geun Han | DATE 28. Jul, 2010 |
|---|-----------------------|-------------------------------|-----------------------|

LCD Business

Samsung Electronics Co . , LTD.

| | | | | | |
|--------------|-------------------|----------------|---------------------------|-------------|-------------|
| MODEL | LTA400HM08 | Doc. No | 06- 000- G- 100728 | Page | 1/25 |
|--------------|-------------------|----------------|---------------------------|-------------|-------------|

**Contents****Samsung Secret**

| | |
|--|------|
| General Description | (3) |
| General Information | (3) |
| 1. Absolute Maximum Ratings | (4) |
| 2. Optical Characteristics | (5) |
| 3. Electrical Characteristics | (8) |
| 3.1 TFT LCD Module | |
| 3.2 Back Light Unit | |
| 3.3 Inverter Input & Specification | |
| 4. Input Terminal Pin Assignment | (11) |
| 4.1 Input Signal & Power | |
| 4.2 Inverter Input Pin Configuration | |
| 4.3 Inverter Input Power Sequence | |
| 4.4 LVDS Interface | |
| 4.5 Input Signals, Basic Display Colors and Gray Scale of Each Color | |
| 5. Interface Timing | (16) |
| 5.1 Timing Parameters (DE mode) | |
| 5.2 Spread Spectrum | |
| 5.3 LVDS Input Data Position | |
| 5.4 Timing diagrams of interface signal | |
| 5.5 Power ON/OFF Sequence | |
| 6. Outline Dimension | (19) |
| 7. Packing | (21) |
| 8. Marking & Others | (22) |
| 9. General Precaution | (23) |
| 9.1 Handling | |
| 9.2 Storage | |
| 9.3 Operation | |
| 9.4 Operation Condition Guide | |
| 9.5 Others | |

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****2/25**

General Description

Samsung Secret

Description

LTA400HM08 is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT(Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit and a back light unit. The resolution of a 40.0" is 1920 x 1080 and this model can display up to 16.7 Billion colors with wide viewing angle of 89° or higher in all directions. This panel is intended to support applications to provide a excellent performance for Flat Panel Display such as Home-alone Multimedia TFT-LCD TV and High Definition TV

Features

- RoHS compliance (Pb-free)
- High contrast ratio & aperture ratio with wide color gamut
- SPVA(Super Patterned Vertical Align) mode
- Wide viewing angle ($\pm 178^\circ$)
- High speed response
- FHD resolution (16:9)
- Low Power consumption
- Edge Type LED (Light Emitted Diode) BLU
- DE (Data Enable) mode
- 2ch LVDS (Low Voltage Differential Signaling) interface (2pixel/clock)

General Information

| Items | Specification | Unit | Note |
|---------------------|---|-------------------|---------|
| Module Size | 943.7 (H _{TYP}) x 560.2 (V _{TYP}) | mm | ± 1.0mm |
| | TBD (Max.) | | |
| Weight | 9,700 (Max.) | g | |
| Pixel Pitch | 0.46125(H) x 0.46125(W) | mm | |
| Active Display Area | 885.6 x 498.15 | mm | |
| Surface Treatment | Haze 7%, Anti-glare | | |
| Display Colors | 8bit – 16.7M | colors | |
| Number of Pixels | 1920 x 1080 | pixel | |
| Pixel Arrangement | RGB vertical stripe | | |
| Display Mode | Normally Black | | |
| Luminance of White | 430 (Typ.) | cd/m ² | |

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****3/25**

Samsung Secret

1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage to the device.

| Item | Symbol | Min. | Max. | Unit | Note |
|-------------------------------|-----------|---------|------|------|------|
| Power Supply Voltage | V_{DD} | GND-0.5 | 13.2 | V | (1) |
| Dimming Control | Max. Lum | - | 5 | V | |
| Storage temperature | T_{STG} | -20 | 60 | °C | (2) |
| Operating temperature | T_{OPR} | 0 | 50 | °C | |
| Surface temperature | T_{SUR} | 0 | 60 | °C | (3) |
| Shock (non - operating) | X,Y,Z | - | 50 | G | (4) |
| Vibration (non - operating) | V_{NOP} | - | 1.5 | G | (5) |

Note (1) $T_a = 25 \pm 2$ °C

(2) Temperature and relative humidity range are shown in the figure below.

a. 90 % RH Max. ($T_a \leq 39$ °C)

b. Relative Humidity is 90% or less. ($T_a > 39$ °C)

c. No condensation

(3) Although abnormal visual problems can be occurred in T_{SUR} range, the polarizer is not damaged in this range.

(4) 11ms, sine wave, one time for $\pm X, \pm Y, \pm Z$ axis

(5) 10-300 Hz, Sweep rate 10min, 30min for X,Y,Z axis




Fig. Temperature and Relative humidity range

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****4/25**

2. Optical Characteristics

Samsung Secret

The optical characteristics should be measured in a dark room or equivalent.

Measuring equipment : TOPCON RD-80S, TOPCON SR-3, ELDIM EZ-Contrast

(Ta = 25 ± 2 °C, VDD=12V, fv= 60Hz, f_{DCLK} = 148.5MHz, Duty = Max)

| Item | | Symbol | Condition | Min. | Typ. | Max. | Unit | Note |
|---|--------|------------------|---|---------------|-------|---------------|-------------------|--------------------|
| Contrast Ratio (Center of screen) | | C/R | | TBD | 4000 | - | | (1) SR-3 |
| Response Time | G-to-G | Tg | Normal q $\mathbf{L,R}$ =0 q $\mathbf{U,D}$ =0 Viewing Angle | - | 8 | - | msec | (3) RD-80S |
| Luminance of White (Center of screen) | | Y _L | | TBD | 430 | - | cd/m ² | (4) SR-3 |
| Color Chromaticity (CIE 1931) | Red | Rx | | TYP. -0.03 | TBD | TYP. +0.03 | | (5),(6) SR-3 |
| | | Ry | | | TBD | | | |
| | Green | Gx | | | TBD | | | |
| | | Gy | | | TBD | | | |
| | Blue | Bx | | | TBD | | | |
| | | By | | | TBD | | | |
| | White | Wx | | | 0.280 | | | |
| | | Wy | | | 0.290 | | | |
| Color Gamut | | - | - | 72 | - | % | (5) SR-3 | |
| Color Temperature | | - | - | 10,000 | - | K | | |
| Viewing Angle | Hor. | q _L | C/R≥10 | 75 | 89 | - | Degree | (6) EZ-Contrast |
| | | q _R | | 75 | 89 | - | | |
| | Ver. | q _U | | 75 | 89 | - | | |
| | | q _D | | 75 | 89 | - | | |
| White Brightness Uniformity (9 Points) | | B _{uni} | | - | - | 25 | % | (2) SR-3 |

- Test Equipment Setup


The measurement should be executed in a stable, windless and dark room between 40min and 60min after lighting the back light at the given temperature for stabilization of the back light. This should be measured in the center of screen.

Environment condition : Ta = 25 ± 2 °C


MODEL
LTA400HM08
Doc. No
06- 000- G- 100728
Page
5/25

Samsung Secret

| Photo detector | Field |
|----------------|-------|
| SR-3 | 2° |
| RD-80S | 1° |



- Definition of test point



Note (1) Definition of Contrast Ratio (C/R)

: Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel

$$C/R = \frac{G_{\max}}{G_{\min}}$$

Gmax : Luminance with all pixels white

Gmin : Luminance with all pixels black

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****6/25**

Samsung Secret


Note (2) Definition of 9 points brightness uniformity (Test pattern : Full White)

$$B_{uni} = 100 * \frac{(B_{max} - B_{min})}{B_{max}}$$

Bmax : Maximum brightness

Bmin : Minimum brightness

Note (3) Definition of Response time : Sum of Tr, Tf




Note (4) Definition of Luminance of White : Luminance of white at center point ⑤

Note (5) Definition of Color Chromaticity (CIE 1931)

Color coordinate of Red, Green, Blue & White at center point ⑤

Note (6) Definition of Viewing Angle

: Viewing angle range (C/R ≥ 10)

**MODEL****LTA400HM08****Doc. No****06- 000- G- 100728****Page****7/25**

3. Electrical Characteristics

Samsung Secret

3.1 TFT LCD Module

The connector for display data & timing signal should be connected.

$T_a = 25^{\circ}\text{C} \pm 2^{\circ}\text{C}$


| Item | | Symbol | Min. | Typ. | Max. | Unit | Note |
|-------------------------|---------------|-------------------|-------|-------|-------|------|---------|
| Voltage of Power Supply | | V _{DD} | 10.8 | 12.0 | 13.2 | V | (1) |
| Current of Power Supply | (a) Black | I _{DD} | - | 600 | 750 | mA | (2),(3) |
| | (b) White | | - | 1050 | 1250 | mA | |
| | (c) N-Pattern | | - | 950 | 1100 | mA | |
| Vsync Frequency | | f _V | 48.0 | 60.0 | 62.0 | Hz | |
| Hsync Frequency | | f _H | 50.0 | 67.5 | 75.0 | kHz | |
| Main Frequency | | f _{DCLK} | 130.0 | 148.5 | 155.0 | MHz | |
| Rush Current | | I _{RUSH} | - | - | 3 | A | (4) |

Note (1) The ripple voltage should be controlled under 10% of V_{DD} .

(2) $f_V=60\text{Hz}$, $f_{DCLK} = 148.5\text{MHz}$, $V_{DD} = 12.0\text{V}$, DC Current.

(3) Power dissipation check pattern (LCD Module only)


a) Black Pattern




b) White Pattern



c) N-Pattern



(4) Measurement Conditions



Rush Current I_{RUSH} can be measured when T_{RUSH} is $470 \mu\text{s}$.

MODEL

LTA400HM08

Doc. No

06- 000- G- 100728

Page


8/25

Samsung Secret

3.2 Back Light Unit

The back light unit contains Edge type White LEDs (Light Emitting Diode)

Ta=25 ± 2℃



| Item | Symbol | Min. | Typ. | Max. | Unit | Note |
|---------------------|--------|------|--------|------|------|------|
| Operating Life Time | Hr | - | 30,000 | - | Hour | (1) |

Note (1) It is defined as the time to take until the brightness reduces to 50% of its original value.

[Operating condition : Ta = 25± 2℃]

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****9/25**

3.3 Inverter Input Condition & Specification

Samsung Secret

| Items | Symbol | Conditions | Specifications | | | Unit | Note |
|------------------|--------------------|--|----------------|------|------|-------|--------------------|
| | | | Min. | Typ. | Max. | | |
| Input Voltage | V _{in} | - | 22 | 24 | 26 | V | Ta=25± 2 °C (3) |
| Input Current | I _{RUSH} | V _{in} =24.0V V _{dim} =3.3V | - | - | 3.6 | A | (1) |
| LED Current | I _{O,MAX} | V _{dim} =3.3 V | 125 | 130 | 135 | mArms | (2) |
| Backlight On/Off | ON | V _{in} =24.0 V | 2.4 | - | 5.25 | V | (3) |
| | OFF | V _{in} =24.0 V | 0 | - | 0.8 | | |
| Dimming Control | V _{DIM} | Max Lum | 3.3 | - | - | V | (3) |
| | | Min. Lum | - | - | 0 | | |

Note) Power Consumption is measured when 430 [cd/m] of luminance which is the typical luminance.

Lamp Current is measured at the point before Lamp.


(1) Max Value of the Power Consumption is measured during initial turn on time* of the backlight

(2) Max Value of the Power Consumption is measured after 60 min warm-up.

(3) The ripple voltage should be controlled under 10% of Input Signal

(4) Duty = On/(On+Off) * 100

* Initial turn-on time : From 0sec to 60min after turn-on

**MODEL****LTA400HM08****Doc. No****06- 000- G- 100728****Page****10/25**

4. Input Terminal Pin Assignment

Samsung Secret

4.1 Input Signal & Power

Connector : FI-RE51S-HF (JAE/UJU)

| Pin | Description | | Pin | Description | |
|-----|-------------------------|---------------|-----|------------------------|---------------|
| 1 | Vdd(12V) | | 26 | EVEN LVDS SIGNAL | RxE[0]P |
| 2 | Vdd(12V) | | 27 | | RxE[1]N |
| 3 | Vdd(12V) | | 28 | | RxE[1]P |
| 4 | Vdd(12V) | | 29 | | RxE[2]N |
| 5 | Vdd(12V) | | 30 | | RxE[2]P |
| 6 | No Connection *Note (1) | | 31 | | GND |
| 7 | GND | | 32 | | RxECLK- |
| 8 | GND | | 33 | | RxECLK+ |
| 9 | GND | | 34 | | GND |
| 10 | ODD LVDS SIGNAL | RxO[0]N | 35 | | RxE[3]N |
| 11 | | RxO[0]P | 36 | | RxE[3]P |
| 12 | | RxO[1]N | 37 | | No Connection |
| 13 | | RxO[1]P | 38 | | No Connection |
| 14 | | RxO[2]N | 39 | GND | |
| 15 | | RxO[2]P | 40 | No Connection | |
| 16 | | GND | 41 | No Connection | |
| 17 | | RxOCLK- | 42 | No Connection | |
| 18 | | RxOCLK+ | 43 | No Connection | |
| 19 | | GND | 44 | No Connection | |
| 20 | | RxO[3]N | 45 | LVDS Option * Note(2) | |
| 21 | | RxO[3]P | 46 | No Connection | |
| 22 | | No Connection | 47 | No Connection | |
| 23 | | No Connection | 48 | No Connection | |
| 24 | | GND | 49 | No Connection | |
| 25 | | RxE[0]N | 50 | No Connection | |
| | | | 51 | No Connection | |

Note (1) No Connection: This PINS are only used for SAMSUNG internal using.

MODEL
LTA400HM08
Doc. No
06- 000- G- 100728
Page
11/25

Note) Pin number starts from Right side

Samsung Secret





Fig. Connector diagram

- a. All GND pins should be connected together and also be connected to the LCD's metal chassis.
- b. All power input pins should be connected together.
- c. All NC pins should be separated from other signal or power.

Note(2) LVDS OPTION : If this PIN HIGH (3.3V) → Normal LVDS format
 LOW (GND) → JEIDA LVDS format

SEQUENCE : On = VDD(T1) → LVDS Option → Interface Signal(T2)
 OFF = Interface Signal(T3) → LVDS Option → VDD



| MODEL | LTA400HM08 | Doc. No | 06- 000- G- 100728 | Page | 12/25 |
|-------|------------|---------|--------------------|------|-------|
|-------|------------|---------|--------------------|------|-------|

4.2. Inverter Input Pin Configuration


Samsung Secret

Connector : Yeon-ho, 20022WR-14B1

| Pin No. | Pin Configuration (FUNCTION) |
|---------|---|
| | Master |
| 1 | 24 V |
| 2 | 24 V |
| 3 | 24 V |
| 4 | 24 V |
| 5 | 24 V |
| 6 | GND |
| 7 | GND |
| 8 | GND |
| 9 | GND |
| 10 | GND |
| 11 | No Connection * Note (1) |
| 12 | Backlight On /Off [ON:2.4 – 5.25 V, OFF: 0 - 0.8 V] |
| 13 | Dimming Control [0V:Min, 3.3V:Max] |
| 14 | No Connection |

Note(1) No connection : This Pins are only used for SAMSUNG internal using

4.3. Inverter Input Power Sequence



Note) SEQUENCE : On = Vin(24V) > Internal or External PWN ≥ Backlight On/off
 OFF = Backlight On/Off ≥ Internal or External PWN > Vin(24V)

MODEL
LTA400HM08
Doc. No
06- 000- G- 100728
Page
13/25



4.4 LVDS Interface

Samsung Secret

- LVDS Receiver : Tcon (merged)
- Data Format (JEIDA & Normal)

| | LVDS pin | JEIDA -DATA | Normal -DATA |
|-------------|--------------|-------------|--------------|
| TxOUT/RxIN0 | TxIN/RxOUT0 | R2 | R0 |
| | TxIN/RxOUT1 | R3 | R1 |
| | TxIN/RxOUT2 | R4 | R2 |
| | TxIN/RxOUT3 | R5 | R3 |
| | TxIN/RxOUT4 | R6 | R4 |
| | TxIN/RxOUT6 | R7 | R5 |
| | TxIN/RxOUT7 | G2 | G0 |
| TxOUT/RxIN1 | TxIN/RxOUT8 | G3 | G1 |
| | TxIN/RxOUT9 | G4 | G2 |
| | TxIN/RxOUT12 | G5 | G3 |
| | TxIN/RxOUT13 | G6 | G4 |
| | TxIN/RxOUT14 | G7 | G5 |
| | TxIN/RxOUT15 | B2 | B0 |
| | TxIN/RxOUT18 | B3 | B1 |
| TxOUT/RxIN2 | TxIN/RxOUT19 | B4 | B2 |
| | TxIN/RxOUT20 | B5 | B3 |
| | TxIN/RxOUT21 | B6 | B4 |
| | TxIN/RxOUT22 | B7 | B5 |
| | TxIN/RxOUT24 | HSYNC | HSYNC |
| | TxIN/RxOUT25 | VSNC | VSNC |
| | TxIN/RxOUT26 | DEN | DEN |
| TxOUT/RxIN3 | TxIN/RxOUT27 | R0 | R6 |
| | TxIN/RxOUT5 | R1 | R7 |
| | TxIN/RxOUT10 | G0 | G6 |
| | TxIN/RxOUT11 | G1 | G7 |
| | TxIN/RxOUT16 | B0 | B6 |
| | TxIN/RxOUT17 | B1 | B7 |
| | TxIN/RxOUT23 | RESERVED | RESERVED |

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****14/25**

Samsung Secret

4.5 Input Signals, Basic Display Colors and Gray Scale of Each Color

| COLOR | DISPLAY (8bit) | DATA SIGNAL | | | | | | | | | | | | | | | | | | | | | | | | | | GRAY SCALE LEVEL |
|------------------------------|-------------------|-------------|----|----|----|----|----|----|----|-------|----|----|----|----|----|----|----|------|----|----|----|----|----|----|----|-------------|--|------------------------|
| | | RED | | | | | | | | GREEN | | | | | | | | BLUE | | | | | | | | | | |
| | | R0 | R1 | R2 | R3 | R4 | R5 | R6 | R7 | G0 | G1 | G2 | G3 | G4 | G5 | G6 | G7 | B0 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | | | |
| BASIC COLOR | BLACK | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - | | |
| | BLUE | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | | |
| | GREEN | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - | | |
| | CYAN | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | | |
| | RED | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - | | |
| | MAGENTA | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | | |
| | YELLOW | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | - | | |
| | WHITE | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | - | | |
| GRAY SCALE OF RED | BLACK | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R0 | | |
| | DARK ↑ | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R1 | | |
| | | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R2 | | |
| | | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | R3~ R252 | | |
| | | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | | | | |
| | ↓ LIGHT | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R252 | | |
| | | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R252 | | |
| | RED | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | R252 | | |
| GRAY SCALE OF GREEN | BLACK | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G0 | | |
| | DARK ↑ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G1 | | |
| | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G2 | | |
| | | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | G3~ G252 | | |
| | | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | | | | |
| | ↓ LIGHT | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G252 | | |
| | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G252 | | |
| | GREEN | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | G252 | | |
| GRAY SCALE OF BLUE | BLACK | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | B0 | | |
| | DARK ↑ | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | B1 | | |
| | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | B2 | | |
| | | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | B3~ B252 | | |
| | | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | | | | |
| | ↓ LIGHT | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | B252 | | |
| | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | B252 | | |
| | BLUE | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | B252 | | |

Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****15/25**

Samsung Secret

5. Interface Timing

5.1 Timing Parameters (DE mode)

| SIGNAL | ITEM | SYMBOL | Min | Typ | Max | UNIT | NOTE |
|--------------------------------|------------------|--------|-------|-------|-------|--------|------|
| Clock | Frequency | 1/TC | 130.0 | 148.5 | 155.0 | MHz | - |
| Hsync | | Fh | 50.0 | 67.5 | 75.0 | KHz | (3) |
| Vsync | | Fv | 48.0 | 60.0 | 62.0 | Hz | |
| Vertical Active Display Term | Display Period | TVD | - | 1080 | - | Lines | - |
| | Vertical Total | TV | 1092 | 1125 | 1380 | Lines | - |
| Horizontal Active Display Term | Display Period | THD | - | 1920 | - | Clocks | - |
| | Horizontal Total | TH | 2092 | 2200 | 2348 | Clocks | - |

Note) This product is DE mode. The input of Hsync & Vsync signal must be inputted.

(1) Test Point : TTL control signal and CLK at LVDS Tx input terminal in system

(2) Internal $V_{DD} = 3.3V$

(3) Hsync / Vsync is following VESA Standard

5.2 Spread Spectrum

- Modulation rate (max) : $\pm 1.5 \%$
- Modulation Frequency : Under 100khz


5.3 LVDS Input Data Position (T-CON)

| ITEM | | SYMBOL | Min. | Typ. | Max. | UNIT | NOTE |
|----------------------------|----------------|------------|------|------|------|------|------|
| Input Data Position | $F_{IN}=80MHz$ | t_{RSM} | - | - | 350 | ps | - |
| | $F_{IN}=74MHz$ | | - | - | 400 | ps | |
| | $F_{IN}=72MHz$ | | - | - | 400 | ps | |
| Input Data Position | $F_{IN}=80MHz$ | t_{RSLM} | -350 | - | - | ps | |
| | $F_{IN}=74MHz$ | | -400 | - | - | ps | |
| | $F_{IN}=72MHz$ | | -400 | - | - | ps | |
| Input common mode voltage | | V_{CM} | 0.3 | - | 1.8 | V | - |
| Differential Input Voltage | | $ V_{ID} $ | 200 | 350 | 600 | mV | - |

Note) When the skew is measured the Spread Spectrum should be 0%

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****16/25**


5.4 Timing diagrams of interface signal (DE mode)

Samsung Secret**MODEL****LTA400HM08****Doc. No****06- 000- G- 100728****Page****17/25**

5.5 Power ON/OFF Sequence

Samsung Secret

To prevent a latch-up or DC operation of the LCD Module, the power on/off sequence should be as the diagram below.



T₁ : V_{DD} rising time from 10% to 90%

T₂ : The time from V_{DD} to valid data at power ON.

T₃ : The time from valid data off to V_{DD} off at power Off.

T₄ : V_{DD} off time for Windows restart

T₅ : The time from valid data to B/L enable at power ON.

T₆ : The time from valid data off to B/L disable at power Off.

- The supply voltage of the external system for the Module input should be the same as the definition of V_{DD}.
- Apply the lamp voltage within the LCD operation range. When the back light turns on before the LCD operation or the LCD turns off before the back light turns off, the display may momentarily show abnormal screen.
- In case of V_{DD} = off level, please keep the level of input signals low or keep a high impedance.
- T₄ should be measured after the Module has been fully discharged between power off and on period.
- Interface signal should not be kept at high impedance when the power is on.
- In Case T₅ is less than 1000msec and T₆ is less than 100msec, Garbage Display can be seen. (It is not related to electrical function issue, Just for recommendation to prevent Garbage Display)

MODEL

LTA400HM08

Doc. No

06- 000- G- 100728

Page

18/25



Samsung Secret


7. PACKING

7.1 CARTON (Internal Package)

(1) Packing Form

Corrugated fiberboard box and corrugated cardboard as shock absorber

(2) Packing Method



7.2 Packing Specification

| Item | Specification | Remark |
|---------------------|---------------------------------|--|
| LCD Packing | 12 ea / (Packing-Pallet Box) | 1. TBD kg / LCD (12ea) 2. 7 Kg / Cushion-pallet (2ea) 3. 6.7 Kg / Packing-Pallet Box (1ea) 4. Cushion-pallet Material : EPS 5. Packing-Pallet Box Material : DW4 |
| Pallet | 1Box / Pallet | 1. Pallet weight = 8kg |
| Packing Direction | Vertical | |
| Total Pallet Size | H x V x height | 1150mm(H) x 985mm(V) x 609mm(height) |
| Total Pallet Weight | TBD kg | Pallet(8kg) + Module (TBD kg) + Cushion (up + bottom =7kg) + Pallet-BOX(6.7kg) |

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****21/25**

Samsung Secret


8. MARKING & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.


(1) Part number : LTA400HM08

(2) Revision: Three letters


(3) Lot number : X X X X XXX XX X



(4) Nameplate Indication



(5) Packing box attach



(6) Others

1. After service part

Lamps cannot be replaced because of the narrow bezel structure.

MODEL

LTA400HM08

Doc. No

06- 000- G- 100728

Page

22/25

9. General Precautions

Samsung Secret

9.1 Handling

- (a) When the Module is assembled, it should be attached to the system firmly using all mounting holes. Be careful not to twist and bend the Module.
- (b) Because the inverter use high voltage, it should be disconnected from power before it is assembled or disassembled.
- (c) Refrain from strong mechanical shock and / or any force to the Module.
In addition to damage, this may cause improper operation or damage to the Module and CCFT back light.
- (d) Note that polarizers are very fragile and could be damage easily.
Do not press or scratch the surface harder than a HB pencil lead.
- (e) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, staining or discoloration may occur.
- (f) If the surface of the polarizer is dirty, clean it using absorbent cotton or soft cloth.
- (g) Desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane.
Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (h) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth . In case of contact with hands, legs or clothes, it must be washed away with soap thoroughly.
- (i) Protect the module from Electrostatic discharge. Otherwise the ASIC IC or semiconductor would be damaged.
- (j) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (k) Do not disassemble the Module.
- (l) Do not disassemble shield case of inverter & LVDS board
- (m) Do not connect N.C pins. (Samsung internal use only)
- (n) Protection film for polarizer on the Module should be slowly peeled off just before use so that the electrostatic charge can be minimized. Must put on antistatic glove while handling a module
- (o) Pins of I/F connector should not be touched directly with bare hands.

| MODEL | LTA400HM08 | Doc. No | 06- 000- G- 100728 | Page | 23/25 |
|-------|------------|---------|--------------------|------|-------|
|-------|------------|---------|--------------------|------|-------|

Samsung Secret

9.2 Storage

- (a) Do not leave the Module in high temperature, and high humidity for a long time.
It is highly recommended to store the Module with temperature from 0 to 35℃ and relative humidity of less than 70%.
- (b) Do not store the TFT-LCD Module in direct sunlight.
- (c) The Module should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light in storing.

9.3 Operation

- (a) Do not connect or disconnect the Module in the "Power On" condition.
- (b) Power supply should always be turned on/off by the "Power on/off sequence"
- (c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (d) The cable between the back light connector and its inverter power supply should be connected directly with a minimized length. A longer cable between the back light and the inverter may cause lower luminance of LED and may require higher startup voltage(Vs).

9.4 Operation Condition Guide

- (a) The LCD product should be operated under normal conditions.
Normal condition is defined as below;
 - Temperature : $20 \pm 15^{\circ}\text{C}$
 - Humidity : $55 \pm 20\%$
 - Display pattern : continually changing pattern (Not stationary)
- (b) If the product will be used in extreme conditions such as high temperature, humidity, display patterns or operation time etc., It is strongly recommended to contact SEC for Application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at Airports, Transit Stations, Banks, Stock market, and Controlling systems.

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****24/25**

9.5 Others

Samsung Secret

- (a) Ultra-violet ray filter is necessary for outdoor operation.
- (b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.
- (c) Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on)
Otherwise the Module may be damaged.
- (d) If the Module keeps displaying the same pattern for a long period of time, the image may be "sticked" to the screen.
To avoid image sticking, it is recommended to use a screen saver.
- (e) This Module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.
- (f) Please contact SEC in advance when you display the same pattern for a long time.

MODEL**LTA400HM08****Doc. No****06- 000- G- 100728****Page****25/25**